



Generator Data

NLX-80W

Operating Frequency	233KHz
Power Factor	0.99
Total Harmonic Distortion	<10%
Operating Range (degree F)	-31/194
Rated Life (Hours)	100,000
Rush (Spike) Input Voltage (1 sec)	>600V
Output Voltage	140V p-p
Input Voltage for 120V Model	90~150VAC
Input Voltage for 220V Model	175~265VAC
Input Voltage for 277V Model	250~305VAC

Lamp Data

ARCA 80W

Rated Life (Hours)	100,000
Initial Lumen	6,800
Mean Lumen	6,120
Lumen Maintenance 40% Life	95%
Mercury in Lamp (mg)	4.8
Nominal Coil Temperature (degree F)	185~239
Re-strike Time	.250sec
Color Rendering Index (CRI)	90

NexLume Series

ARCA 80w Lamp & Generator

Adaptive Energy Systems, Inc.
801 S. Figueroa St., # 1060 Los Angeles, CA 90017

SIZE	FSCM NO.	DWG NO. AES-NLXA-80	REV E
------	----------	---------------------	-------

SCALE: Not to scale

SHEET 1 of 1

*Color Temperature Available In: 27=2700k, 35=3500k, 41=4100k, 50=5000k, 60=6000k
*UL Approved : E 306138
*FCC: 200371-9